


IR MOTORIZED VF VANDAL-PROOF DOME CAMERA

DAI-390IP5MVF



- | | | | |
|-------------------------------------|--------------------------------------|------------------------------------|--------------------|
| 1/2.7" CMOS Sensor | ONVIF | 3.3-12mm Motorized with Auto-Focus | I/O |
| 2 Mega-Pixel | True WDR / BLC / HLC | 25m IR Illumination | 2 Way Audio |
| True Day & Night (IR Cut Removable) | 3D Noise Reduction | PoE Support | Technician Port |
| H.265 (HEVC) Compression | Motion Detection and Privacy Masking | Local Storage | IP 66 Protection |
| 0 Lux (IR On) Min. Illumination | Analytics Support | RS-485 | IK 10 Vandal-Proof |

Specifications

Camera		Housing		
Video	Model	DAI-390IP5MVF		
	Image Sensor	1/2.7" CMOS (16:9)		
	Effective Pixels	1920x1080		
	Electronic Shutter	1/25s ~ 1/100000s		
	Frame Rate	1-25/30FPS		
	Day & Night	ICR		
	Min. Illumination	Day: 0.022lux / Night: 0.01lux (@F1.8, AGC On) 0lux with IR on		
	Audio	Audio compression	G.711A/G.711U	
		Communication	Two-way Audio	
	Image Processing	Image Settings	AWB, AGC Adjustable Exposure Mode (Auto) Sharpness, Saturation, Brightness & Contrast Adjustable	
Image Enhancement		True WDR (120dB) / BLC / HLC / ROI		
Noise Reduction		3D-DNR		
Image Orientation		Mirror/Flip		
Privacy Zone		Yes		
Motion Detection		Yes		
Analytics		Camera Tampering, Line Crossing, Sterile Area		
Compression	Video Compression	H.265 / H.264 / MJPEG (Sub-Stream Only)		
	Resolution	1080P (1920x1080), 720P (1280x720), D1, CIF		
	Multi-Stream	11920x1080 / 1280x720 / D1 / CIF / 480x240 (1~25/30FPS)		
	Bit rate	64Kbps ~ 4Mbps@H.265 / 128Kbps ~ 6Mbps@H.264		
	Encode Mode	VBR/CBR		
Image Quality	Five levels under VBR; Free adjustment under CBR			
Connectivity	IR Distance	25m (30 IR LED)		
	Lens (Field of View)	3.3-12mm Motorized with Auto-Focus (109.8°-38.5°)		
	Iris	Fixed Iris		
	Lens Mount	Φ14 mount		
	Protection Rate	Water Proof: IP66 / Vandal Proof: IK10		
	Bracket	3-Axis Gimbal		
	Dimensions	Φ150mm×114mm		
Network	Weight(gross)	880g		
	Network	RJ45 (+PoE)		
	Power	DC Socket		
	Analog Video Output	CVBS(BNCx1)		
	Audio Connectivity	1Ch Input, 1Ch Output		
	SD Card	Event/Schedule based Main/Sub-Stream recording (Up to 128Gb)		
	RS485	Yes		
Others	Alarm	1Ch Input, 1Ch Output		
	Remote Monitoring	IE Browsing, CMS Software, Provision Cam2 Mobile App		
	User Access	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission		
	Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP		
ONVIF	Yes			
Ethernet	100Mbps			
PoE	Yes			
Power Supply	DC12V/~360mA / PoE/~6.2W			
Work Environment	-30 C ~ 50 C, 10%~90% Humidity			

