
**elbaC Cable**

ZAC sous le Beer - RD 836
F-27730 BUEIL (Eure - France)
Tél : +33 (0)2 32 62 00 92
Fax : +33 (0)2 76 01 31 80
www.elbac.fr / info@elbac.fr

**Construction****Inner conductor** ① - ③

Material	Annealed copper
Diameter	Ø 0,48 mm
Area	0,18 mm ²

Insulation

Material	HDPE
Diameter	Ø 0,85 mm

Assembly

3 pairs	
Colors	See color table
Lay length	

Mylar spiral ④

Coverage	90 %
----------	------

Drain wire ⑤

Material	Tinned copper
Diameter	Ø 0,45 ± 0,008 mm

Screen ⑥

Material	Alu/PET (40µ/12µ)
Coverage	≥ 125 %

Rip Cord ⑦

Material	200D
----------	------

Sheath ⑧

Material	PVC Grey Flame retardant IEC 332-1 (C2)
Diameter	Ø 5,00 mm

Mass	34 kg/km
------	----------

Marking of sheath

Printing	LY6ST/SYT+ 3P AWG24 - CE - with XXX : Quantity in meter still available per reel DDDDD : Date code
Color / Process	Black / Ink jet
Step	1 m

Notes**Electrical characteristics**

Impedance	100 ± 20 Ω
Mutual paires capacitance	70 nF/km
Max conductor DC resistance	96 Ω/km
Propagation velocity ratio	65%
Rated voltage	200V
Insulation resistance 20°C	> 500MΩ.km

Performances

Frequency MHz	Max attenuation dB/100m
1.00	3.00

Frequency MHz	NEXT dB
2.00	40.00

Color table

Pairs	Colors			Lay Length (mm)
	A	B		
①	Light blue/White	White	White	20
②	Light blue/Dark blue	Dark blue	Dark blue	23
③	Light blue/Yellow	Yellow	Yellow	26

Based on NF C93-529 + color line on light blue (A)

Meet Standards

Fire performance :	IEC 60332-1
Environment :	European directive 2011/65/EU
Marking :	CE
Fire reaction :	EN 50575:2014/A1:2016

Thermal characteristics

CPR fire reaction class	E _{ca}
Rated temperature	-15 / 70°C

Mechanical characteristics

Static (d = sheath diameter)	r = 6 × d
Dynamic (d = sheath diameter)	r = 12 × d

Packaging

- B1	: 100m / Carton Box
- R3	: 300m / Easy Reel Box
- W5	: 500m / Wooden Drum