


30M IR FIXED LENS BULLET CAMERA

I3-250IP536



1/2.5" CMOS Sensor
5 Mega-Pixel
True Day & Night (IR Cut Removable)
H.265 (HEVC) Compression
0 Lux (IR On) Min. Illumination

ONVIF
True WDR / BLC / HLC
3D Noise Reduction
Motion Detection and Privacy Masking
Analytics Support

3.6mm Mega-Pixel Lens
30m IR Illumination
PoE Support
1 Way Audio
CVBS

Specifications

Camera	Video	Model	I3-250IP536
		Image Sensor	1/2.5" CMOS (4:3)
		Effective Pixels	2592x1944
		Electronic Shutter	1/25s ~ 1/100000s
		Frame Rate	Standard: 1-25/30 (True-WDR), HFR*: 1-50/60 (Max. 1080P & D-WDR)
		Day & Night	ICR
		Min. Illumination	Day: 0.013lux / Night: 0.003lux (@F1.2, AGC On)
	Audio	Audio compression	G.711A/G.711U
		Communication	One-way Audio
	Image Processing	Image Settings	AWB, AGC Adjustable, Exposure Mode (Auto) Sharpness, Saturation, Brightness & Contrast Adjustable
		Image Enhancement	True WDR (120dB, HFR* Disabled) / BLC / HLC / ROI
		Noise Reduction	3D-DNR
		Image Orientation	Mirror/Flip
		Privacy Zone	Yes
		Motion Detection	Yes
	Analytics	Analytics	Camera Tampering, Line Crossing, Sterile Area, Object Monitoring
	Compression	Video Compression	H.265 / H.264
		Resolution	5MP(2592x1944), 4MP(2560x1440), 1080P, 720P, D1, CIF, 480x240
		Multi-Stream	5MP / 4MP / 1920x1080 / 1280x720 / D1 / CIF / 480x240 (1~25/30FPS / 1~50/60FPS with HFR*)
		Bit rate	64Kbps ~ 8Mbps@H.265 / 128Kbps ~ 10Mbps@H.264
		Encode Mode	VBR/CBR
		Image Quality	Five levels under VBR; Free adjustment under CBR

*HFR (High Frame Rate) must be supported by the NVR in order to work properly.

Housing	IR Distance	30m (42 IR LED)
	Lens (Field of View)	3.6mm (84.5°)
	Iris	Fixed Iris
	Lens Mount	Φ14 mount
	Protection Rate	Water Proof: IP66
	Bracket	3-Axis Wall Bracket
	Dimensions	Φ87mm×219mm
	Weight(gross)	635g
Connectivity	Network	RJ45 (+PoE)
	Power	DC Socket
	Analog Video Output	CVBS (BNCx1)
	Audio Connectivity	1Ch Input
	SD Card	No
	RS485	No
	Alarm	No
Network	Remote Monitoring	IE Browsing, CMS Software, Provision Cam2 Mobile App
	User Access	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission
	Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP
	ONVIF	Yes
	Ethernet	100Mbps
Others	PoE	Yes
	Power Supply	DC12V/~500mA / PoE/~6.5W
	Work Environment	-30 C ~50 C, 10%~90% Humidity

